

DESCRIPTION


The N-8061MS is a surface-mount master station designed to operate in conjunction with TOA IP Intercom Exchange and features high quality hands-free conversation.

SPECIFICATIONS

* 0 dB = 1 V

Power Source	48 V DC (supplied from the IP intercom exchange (option))
Power Consumption	1.8 W (at rated), 2.4 W (max.)
Wiring Method	Non-polar one pair stranded wire system
Transmission System	2 wire 160 kbps echo canceller transmission system
Signal Level	Under 0 dB*
Speech Method	Hands-free conversation
Audio Frequency Range	300 - 7,000 Hz
Transmission Range	Max. 1500 m (ø0.65 mm, Loop resistance 170 Ω)
Hands-free	Speaker: 8 Ω, over 0.6 W (external speaker) Microphone: Omni-directional electret condenser microphone
Line Connecting Terminal	Pin header (2 pins)
External Speaker Connecting Terminal	Solderless connector (2 pins, male)
Installation Method	Surface-mount
Operating Temperature	0°C to +40°C
Operating Humidity	Under 90% RH (no condensation)
Housing Protection	BS EN62262: 2002: IK04 equivalent
Dust/Water Protection	IP54 equivalent
Resistance to Environment	Passed our gas corrosion test
Finish	Body: ABS resin, gray
Dimensions	200 (W) × 300 (H) × 143.5 (D) mm
Weight	2.55 kg
Accessory	Wall mounting screw ×4

APPEARANCE



UNIT:mm SCALE: 1/3