

Article No.	Article Description	Rated input	SPL (1W, 1m)	Frequency response	Coverage angle		CPD-Nr.
					Horizontal	Vertical	
BS-678BSB	Wall Mount Speakers	6 W (100 V), 3 W (70 V)	94 dB	150 - 18,000 Hz	360° (500 Hz), 135° (1000 Hz), 130° (2000 Hz), 70° (4000 Hz)	330° (500 Hz), 160° (1000 Hz), 135° (2000 Hz), 70° (4000 Hz)	0359/CPD/0103
BS-678BSW	Wall Mount Speakers	6 W (100 V), 3 W (70 V)	94 dB	150 - 18,000 Hz	360° (500 Hz), 135° (1000 Hz), 130° (2000 Hz), 70° (4000 Hz)	330° (500 Hz), 160° (1000 Hz), 135° (2000 Hz), 70° (4000 Hz)	0359/CPD/0103
BS-680FC	Wall Mount Speakers, EN 54-24 certified version	6 W (100 V), 3 W (70 V)	94 dB	150 - 20,000 Hz	180° (500 Hz), 140° (1000 Hz), 120° (2000 Hz), 100° (4000 Hz)	180° (500 Hz), 140° (1000 Hz), 110° (2000 Hz), 80° (4000 Hz)	1438/CPD/0178
BS-1015BSB	Wall Mount Speakers, EN 54-24 certified version	15 W	90 dB	80 - 20,000 Hz	220° (500 Hz), 150° (1000 Hz), 120° (2000 Hz), 90° (4000 Hz)	330° (500 Hz), 160° (1000 Hz), 120° (2000 Hz), 70° (4000 Hz)	0359/CPD/0104
BS-1015BSW	Wall Mount Speakers, EN 54-24 certified version	15 W	90 dB	80 - 20,000 Hz	220° (500 Hz), 150° (1000 Hz), 120° (2000 Hz), 90° (4000 Hz)	330° (500 Hz), 160° (1000 Hz), 120° (2000 Hz), 70° (4000 Hz)	0359/CPD/0104
BS-1034EN	Wall Mount Speakers, EN 54-24 certified version	10 W	89 dB	120 - 20,000 Hz	360° (500 Hz), 150° (1000 Hz), 115° (2000 Hz), 100° (4000 Hz)	300° (500 Hz), 130° (1000 Hz), 160° (2000 Hz), 80° (4000 Hz)	0359/CPD/0102
CS-64BS	Splashproof projection Speakers, EN 54-24 certified version	6 W (100 V / 70 V)	96 dB	130 - 13,000 Hz	360° (500 Hz), 210° (1000 Hz), 85° (2000 Hz), 45° (4000 Hz)	360° (500 Hz), 210° (1000 Hz), 85° (2000 Hz), 45° (4000 Hz)	0359/CPD/0107
CS-154BS	Splashproof projection Speakers, EN 54-24 certified version	15 W (100 V / 70 V)	97 dB	150 - 15,000 Hz	140° (500 Hz), 90° (1000 Hz)	200° (500 Hz), 155° (1000 Hz), 90° (2000 Hz), 60° (4000 Hz)	0359/CPD/0108
F-1000BTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	15 W	87 dB	85 - 20,000 Hz	Directivity angle: 90°	Directivity angle: 90°	1438/CPD/0282
F-1000WTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	15 W	87 dB	85 - 20,000 Hz	Directivity angle: 90°	Directivity angle: 90°	1438/CPD/0282
F-1300BTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	30 W	90 dB	80 - 20,000 Hz	Directivity angle: 110°	Directivity angle: 110°	1438/CPD/0282
F-1300WTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	30 W	80 dB	80 - 20,000 Hz	Directivity angle: 110°	Directivity angle: 110°	1438/CPD/0282
F-2000BTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	60 W	92 dB	65 - 20,000 Hz	Directivity angle: 110°	Directivity angle: 100°	1438/CPD/0282
F-2000WTWP EB-Q	Fashion Speaker System weatherproof, EN-24 certified version	60 W	92 dB	65 - 20,000 Hz	Directivity angle: 110°	Directivity angle: 100°	1438/CPD/0282
PC-1869EN	Ceiling Mount Speakers EN 54-24 certified version	6 W (100 V), 3 W (70 V)	94 dB	100 - 18,000 Hz	165° (500 Hz), 175° (1000 Hz), 165° (2000 Hz), 70° (4000 Hz)	165° (500 Hz), 175° (1000 Hz), 165° (2000 Hz), 70° (4000 Hz)	0359/CPD/0100
PC-1867FC	Firedome Ceiling Mount Speaker, EN-24 certified version	6 W (100 V), 3 W (70 V)	90 dB	100 - 16,000 Hz	186° (500 Hz), 178° (1000 Hz), 148° (2000 Hz), 76° (4000 Hz)		1438/CPD/0183
PC-2369EN	Ceiling Mount Speakers, EN 54-24 certified version	6 W (100 V), 3 W (70 V)	94 dB	70 - 18,000 Hz	160° (500 Hz), 170° (1000 Hz), 160° (2000 Hz), 60° (4000 Hz)	160° (500 Hz), 170° (1000 Hz), 160° (2000 Hz), 60° (4000 Hz)	0359/CPD/0101
PE-154EN	Pendant Speakers, EN 54-24 certified version	15 W (100 V), 7.5 W (70 V)	91 dB	70 - 20,000 Hz	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	0359/CPD/0105
PE-154BS	Pendant Speakers, EN 54-24 certified version	15 W (100 V), 7.5 W (70 V)	91 dB	70 - 20,000 Hz	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	0359/CPD/0105
PJ-154BS	Projection Speakers, EN 54-24 certified	15 W (100 V), 7.5 W (70 V)	91 dB	70 - 20,000 Hz	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	360° (500 Hz), 170° (1000 Hz), 90° (2000 Hz), 70° (4000 Hz)	0359/CPD/0106
SC-615BS	Reflex Horn Speaker, EN 54-24 certified version	15 W	109 dB	315 - 12,500 Hz	360° (500 Hz), 160° (1000 Hz), 85° (2000 Hz), 45° (4000 Hz)	360° (500 Hz), 200° (1000 Hz), 115° (2000 Hz), 60° (4000 Hz)	0359/CPD/0109
SC-630M EU	Reflex Horn Speaker, EN 54-24 certified version						1438/CPD/0280
HX-5B-WP EU	Compact Array, EN-54-24 certified version	200 W (Continuous pink noise) 600 W (continuous program)	96 dB (60°), 97 dB (45°), 98 dB (30°), 99 dB (15°)	95 - 20,000 Hz (60°), 100 - 20,000 Hz (45°), 105 - 20,000 Hz (30°), 110 - 20,000 Hz (15°)	Directivity angle: 100° (2000 Hz or more)	Directivity angle: 60° (800 Hz or more), 45° (1200 Hz or more), 30° (1600 Hz or more), 15° (3200 Hz or more)	1438/CPD/0281
HX-5W-WP EU	Compact Array, EN-54-24 certified version	200 W (Continuous pink noise) 600 W (continuous program)	96 dB (60°), 97 dB (45°), 98 dB (30°), 99 dB (15°)	95 - 20,000 Hz (60°), 100 - 20,000 Hz (45°), 105 - 20,000 Hz (30°), 110 - 20,000 Hz (15°)	Directivity angle: 100° (2000 Hz or more)	Directivity angle: 60° (800 Hz or more), 45° (1200 Hz or more), 30° (1600 Hz or more), 15° (3200 Hz or more)	1438/CPD/0281
PC-275AB-EB	Surface mount ceiling speaker	6 W (6 W-3 W-1.5 W)	88 dB	130 - 20,000 Hz			1488/CPD/0337/W
PC-245AB-EB	Ceiling speaker with firedome	6 W (6 W-3 W-1.5 W)	88 dB	150 - 20,000 Hz			1488/CPD/0335/W
BS-250AB-EB	Wall speaker	6 W (6 W-3 W-1.5 W)	89 dB	150 - 20,000 Hz			1488/CPD/0336/W
PJ-202DL-EB	Bidirectional projection speaker	20 W (20 W-10 W-5 W)	89 dB	120 - 20,000 Hz			1488/CPD/0338/W